


## Stone Taskworx® Tile

Style Number	<b>5T454</b>	
Collection	<b>Floor Architecture III</b>	
Product Type	<b>Carpet Tile</b>	
Construction	<b>Standard</b>	<b>Data + Performance</b>
Type of Manufacture	<b>ISO 2424</b>	<b>tufted 1/10"   39.4 per 10cm</b>
Aspect	<b>ISO 2424</b>	<b>Multi-Level Pattern Loop</b>
Dye Method	<b>EN 994</b>	<b>100% Solution Dyed</b>
Dimensions	<b>EN 994</b>	<b>50 cm x 50 cm   20 tiles (5 m<sup>2</sup>) per box</b>
Primary Backing	<b>ISO 2424</b>	<b>Pet Non-Woven</b>
Secondary Backing	<b>ISO 2424</b>	<b>Taskworx® Tile   Polymer Modified Bitumen</b>
Pile Fibre Composition	<b>ISO 2424</b>	<b>Eco Solution Q® Polyamide 6</b>
Total Thickness	<b>ISO 1765</b>	<b>6.7 mm</b>
Effective Pile Thickness	<b>ISO 1766</b>	<b>3.3 mm</b>
Total Mass	<b>ISO 8543</b>	<b>3980 g/m<sup>2</sup></b>
Nominal Total Pile Mass	<b>ISO 2424</b>	<b>630 g/m<sup>2</sup></b>
Effective Pile Mass	<b>ISO 8543</b>	<b>354 g/m<sup>2</sup></b>
Pile Density	<b>ISO 8543</b>	<b>0.108 g/cm<sup>3</sup></b>
Total Recycled Content	<b>49% (pre-consumer 49%   post-consumer 0%)</b>	











### Performance

Number of Tufts	<b>ISO 1763</b>	<b>165,000/m<sup>2</sup>   42.0 per 10cm</b>
Electrostatic Propensity	<b>ISO 6356</b>	<b>≤ 2.0 kv (Stroll Test)</b>
Use Classification	<b>EN 1307</b>	<b>33 Commercial Heavy</b>
Luxury Class	<b>EN 1307</b>	<b>LC1</b>
Dimensional Stability	<b>EN 986</b>	<b>≤ 0.2%</b>
Impact Sound Insulation	<b>ISO 10140</b>	<b>26db</b>
Sound Absorption Classification	<b>ISO 354/11654</b>	<b>0.15 αW   Class E</b>
Thermal Resistance m <sup>2</sup> K/W	<b>ISO 8302</b>	<b>0.077 M<sup>2</sup> K/W Tog 0.77</b>
Dry Slip Resistance	<b>ISO 13893</b>	<b>Pass</b>
Colour Fastness To Light	<b>ISO 105-B02</b>	<b>&gt;6</b>
Flammability	<b>EN 13501-1</b>	<b>Bfl-S1 (Adhered Testing)</b>
Castor Chair	<b>EN 985</b>	<b>≥2.4 Continuous Use</b>

15 Year Commercial Limited Warranty subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.

### Recommended Installation Method



 17 EU.DOP/0493/CPR/0621/0422/BT OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905 BL NETHERLANDS (NLD) Notified Body 2895	 22 UK.DOP/0338/CPR/1220/0422/BT SHAW EUROPE LIMITED BLACKADDIE RD, SANQUHAR DG4 6DB, UNITED KINGDOM Approved Body 0338
  	
EN14041:2004/AC:2006 For use as an indoor floor covering as specified by the manufacturer	

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302

## Coordinating Products

Carpet Tile: **Stone Comfortworx® Tile, Fragment Comfortworx® Tile, Formation Colours Comfortworx® Tile, Fragment Colours Comfortworx® Tile, Stone Colours Comfortworx® Tile, Formation Comfortworx® Tile, Fragment Taskworx® Tile, Formation Colours Ecoworx® S Tile, Fragment Colours Ecoworx® S Tile, Formation Colours Taskworx® Tile, Fragment Colours Taskworx® Tile, Fragment Ecoworx® S Tile, Stone Ecoworx® S Tile, Formation Taskworx® Tile, Formation Ecoworx® S Tile, Stone Colours Taskworx® Tile, Stone Colours Ecoworx® S Tile**

## Material Health & Environmental Certifications

Certifications below apply exclusively to the carpet tile rug itself and not the LokWorx Tabs adhesive

Declaration of Performance	<b>EU.DOP/0493/CPR/0621/0422/BT</b>
Country of Origin**	<b>United Kingdom</b>
BREEAM Contribution Credit	<b>Certificate of Approval Schools/Offices/Health/Industrial Shed Retail</b>










## Air Quality

Indoor Air Comfort Gold	<b>Certified</b>
M1	<b>Certified</b>

## Memberships

WGBC Framework	<b>WGBC Framework</b>
UKGBC	<b>UKGBC</b>
Emirates Green Building Council	<b>Emirates Green Building Council</b>
Chemsec	<b>Chemsec</b>

## Light Reflectance Value

					
Marble 53100 LRV 14.5	Azurite 53485 LRV 4.3	Granite 53500 LRV 4.3	Mica 53518 LRV 11.5	Mortar 53530 LRV 29.5	Limestone 53535 LRV 15.4
					
Anthracite 53555 LRV 7.2	Chromite 53580 LRV 10.3	Mix 53597 LRV 7.5			

## Additional Information

---

15 Year Commercial Limited warranty

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](https://shawcontract.com/testing) for more information.

